



## Ruger 22/45 Extended Magazine Bumper (Base Pad) Installation Instructions

V2.0

[www.tandemkross.com](http://www.tandemkross.com)

For more info or support contact [CustomerService@tandemkross.com](mailto:CustomerService@tandemkross.com)

### **Attention:**

**Before you begin be certain that the magazine is clear and safe.** You will need a small punch, allen wrench, or awl for the installation process. Be cautious of the spring and wear safety glasses.

1. Remove the magazine from the magwell and clear the magazine of any rounds. Holding the magazine so that the bottom faces up, you should see the plunger.



2. Using an Allen wrench, or a similar tool, lightly depress the plunger.

3. While the plunger is depressed, use your thumb and gently push the back of magazine base forward. Be mindful of the spring and keep it depressed with your thumb if able.



4. If unable to keep the spring depressed, you should be able to push it back in with your thumb and index finger. Firmly pinch the plunger with your thumb and index finger, and push it down in small increments. Be sure to use your other hand to keep the spring from jumping out.

5. With the spring and plunger fully in the magazine body, depress the plunger with the back of the magazine bumper base pad.



6. With the base pad in position, push it rearwards to slide it in place. You should hear a soft click.

*If you find your spring isn't compressing into the hole as it should, use a 3/16 drill bit to clear it out.*

