



## TANDEMKROSS SW22 Victory “hiveGrip” Wrap Around Grip Installation Instructions

V1.0

[www.tandemkross.com](http://www.tandemkross.com)

For more info or support contact [CustomerService@tandemkross.com](mailto:CustomerService@tandemkross.com)

**Attention: Before you begin, be certain that the firearm is safe.**

*Always wear eye protection when working on firearm parts.*

*Tools you will need:*

- A 3/32 in. allen wrench

1. Remove the grip panels from the SW22 Victory. Set aside the four grip screws as they will be used later.

2. **Be aware.** The bolt stop is free floating and may fall out. If this occurs, align the end of the spring with the highlighted hole in the grip frame and reinsert the bolt stop. **Be aware.** The magazine release is not affixed to the grip frame and may fall out. The magazine release spring is also free floating and may fall out of the right side of the gun. If the occurs, re-install it into the hole in the magazine release on the right side of the gun.



3. Slide the hiveGrip onto the grip frame. The studs on the grip frame (highlighted red) fit into the recesses of the grip panels. Take care to ensure the magazine release spring is sitting flush to the grip face on the right side of the gun when sliding the grip over the frame.



4. Screw in the grip screws from earlier by starting with the top left screw. Press the grip forward as you tighten the top left screw to ensure proper fit under the safety. Next tighten the bottom left, then top right and finally bottom right.

*The hiveGrip is a form fitting grip designed specifically for the SW22 Victory and may need to be gently stretched to align the screw holes.*

